

Mesa Power Strip

product specifications & UL certification

U.S.A. Power Strips SFC306-X Series

The SFC306-X series power strip offers 15 amp, 125V multi-outlet AC power distribution in a convenient 12 to 72 inch mountable housing. Offers horizontal or vertical power distribution in rackmount, raceway, laptops cart and workbench applications, etc. Includes 6 to 16 NEMA 5-15R output receptacles with any inch center-to-center spacing, 5-25 ft AC line cord and lighted power switch with circuit breaker and locking transparent cover to prevent accidental shutoff. Sturdy all-metal extruded aluminum housing stands up to demanding network, laboratory or factory environments.

Certifications & Warranty

CERTIFICATIONS	
UL1363 (Power tap)	UL1363 E336749
cUL / CSA (Canada)	UL & cUL
WARRANTY	
Product warranty period (U.S., Canada & Puerto Rico)	Lifetime limited warranty





Specifications

ОИТРИТ	
Frequency compatibility	60 Hz
Output watts	1800
Output volt amp capacity	15A
Outlet quantity/type	6-16 Nema 5-15R
Outlet spacing	any in.
INPUT	
Recommended electrical service	15A 125V
Input connection type	Nema 5-15P
Input plug features	Black or other
Input cord length (ft.)	5 to 25
Input cord length (in.)	12-1/4 to 72
Input cord gauge, type	14/3 SJT
Voltage compatibility (VAC)	125
LAMP ALARMS & SWITCHES	
Rock switches with circuit breaker and lamp	Lighted 2 position switch controls power to all outlets
Locking switch cover	Transparent on/off switch cover prevents accidental turn-off